Please type a plus sign (+) inside this box → [+]

PTO/SB/05 (12/97)
Approved for use through 09/30/00. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

JC526 U.S. PTO
03/13/98

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.	ROC1-BC20
First Named Inventor or Application Identifier	BEHNAM S. KATIBIAN
Express Mail Label No.	EM322760409US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. [X] Fee Transmittal Form *(Submit an original, and a duplicate for fee processing)*
2. [X] Specification [*Total Pages* 22] *(preferred arrangement set forth below)*
   - Descriptive title of the Invention
   - Cross References to Related Applications
   - Statement Regarding Fed sponsored R & D
   - Reference to Microfiche Appendix
   - Background of the Invention
   - Brief Summary of the Invention
   - Brief Description of the Drawings *(if filed)*
   - Detailed Description
   - Claim(s)
   - Abstract of the Disclosure
3. [X] Drawing(s) *(35 USC 113)* [*Total Sheets* 6]
4. Oath or Declaration [*Total Pages*]
   - a [X] Newly executed (original or copy)
   - b [ ] Copy from a prior application (37 CFR 1.63(d)) *(for continuation/divisional with Box 17 completed)* *[Note Box 5 below]*
     - i. [ ] DELETION OF INVENTOR(S) Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
5. [ ] Incorporation By Reference *(useable if Box 4b is checked)* The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6. [ ] Microfiche Computer Program *(Appendix)*
7. Nucleotide and/or Amino Acid Sequence Submission *(if applicable, all necessary)*
   - a. [ ] Computer Readable Copy
   - b. [ ] Paper Copy (identical to computer copy)
   - c. [ ] Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. [ ] Assignment Papers (cover sheet & document(s))
9. [ ] 37 CFR 3.73(b) Statement *(when there is an assignee)* [X] Power of Attorney
10. [ ] English Translation Document *(if applicable)*
11. [ ] Information Disclosure Statement (IDS)/PTO-1449 [ ] Copies of IDS Citations
12. [ ] Preliminary Amendment
13. [X] Return Receipt Postcard (MPEP 503) *(Should be specifically itemized)*
14. [ ] Small Entity Statement(s) [ ] Statement filed in prior application, Status still proper and desired
15. [ ] Certified Copy of Priority Document(s) *(if foreign priority is claimed)*
16. [ ] Other: .....

17. **If a CONTINUING APPLICATION,** *check appropriate box and supply the requisite information:*
    [ ] Continuation [ ] Divisional [ ] Continuation-in-part (CIP) of prior application No: _____/_____

18. CORRESPONDENCE ADDRESS

[ ] *Customer Number or Bar Code Label* *(Insert Customer No. or Attach bar code label here)* or [X] *Correspondence address below*

NAME	Albin H. Gess Price, Gess & Ubell				
ADDRESS	2100 S.E. Main Street, Suite 250				
CITY	Irvine	*STATE*	CA	*ZIP CODE*	92614-6238
COUNTRY	U.S.A.	*TELEPHONE*	(714) 261-8433	*FAX*	(714) 261-1726

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

Please type a plus sign (+) inside this box → [+]

PTO/SB/29 (12/97)
Approved for use through 09/30/00. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
	TOTAL CLAIMS (37 CFR 1.16(c))	22 -20 =	2	x $ 22 =	$ 44.00
	INDEPENDENT CLAIMS (37 CFR 1.16(b))	3 -3 =	0	x $ 82 =	0
	MULTIPLE DEPENDENT CLAIMS (if applicable) (37 CFR 1.16(d))			+ $ =	
				BASIC FEE (37 CFR 1.16(a))	790.00
				Total of above Calculations =	834.00
	Reduction by 50% for filing by small entity (Note 37 CFR 1.9, 1.27, 1.28).				
				TOTAL =	834.00

6. Small entity status:
   a. ☐ A small entity statement is enclosed.
   b. ☐ A small entity statement was filed in the prior nonprovisional application and such status is still proper and desired.
   c. ☐ Is no longer claimed.
7. The Commissioner is hereby authorized to credit overpayments or charge the following fees to Deposit Account No. 16 - 2462 :
   a. ☒ Fees required under 37 CFR 1.16.
   b. ☐ Fees required under 37 CFR 1.17.
   c. ☐ Fees required under 37 CFR 1.18.
8. ☒ A check in the amount of $ 834.00 is enclosed.
9. ☐ Other: .....

NOTE: *The prior application's correspondence address will carry over to this CPA UNLESS a new correspondence address is provided below.*

10. NEW CORRESPONDENCE ADDRESS

☐ *Customer Number or Bar Code Label* (Insert Customer No. or Attach bar code label here) *or* ☒ *New correspondence address below*

NAME	Albin H. Gess				
	Price, Gess & Ubell				
ADDRESS	2100 S.E. Main Street, Suite 250				
CITY	Irvine	STATE	CA	ZIP CODE	92614-6238
COUNTRY	U.S.A.	TELEPHONE	(714) 261-8433	FAX	(714) 261-9072

11. SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED

NAME	Albin H. Gess Registration No. 25,726
SIGNATURE	
DATE	March 13, 1998

JOSEPH W. PRICE
ALBIN H. GESS
FRANKLIN D. UBELL
DOYLE B. JOHNSON
MICHAEL J. MOFFATT
GORDON E. GRAY III
BRADLEY D. BLANCHE*
SANDRA M. PARKER

*ADM. VA ONLY

PRICE, GESS & UBELL

ATTORNEYS AT LAW

2100 S.E. MAIN STREET, SUITE 250

IRVINE, CALIFORNIA 92614-6238

A PROFESSIONAL CORPORATION
TELEPHONE: (714) 261-8433
FACSIMILE. (714) 261-9072
FACSIMILE: (714) 261-1726

e-mail: pgu@ix.netcom.com

PATENT APPLICATION

Applicant: BEHNAM S. KATIBIAN, et al.

For: METHOD AND APPARATUS FOR LOW-COST LINE-BASED VIDEO COMPRESSION OF DIGITAL VIDEO STREAM DATA

Attorneys' Docket: ROC1-BC20/97RSS423

EXPRESS MAIL LABEL NO. EM322760409US

DATE OF DEPOSIT: March 13, 1998

PATENT APPLICATION

ROC1-BC20/97RSS423

METHOD AND APPARATUS FOR LOW COST LINE-BASED VIDEO COMPRESSION OF DIGITAL VIDEO STREAM DATA

Behnam S. Katibian
Magued M. Bishay

METHOD AND APPARATUS FOR LOW COST LINE-BASED VIDEO COMPRESSION OF DIGITAL VIDEO STREAM DATA

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates generally to image processing and more specifically pertains to a video compression algorithm for increasing the data throughput on a limited bandwidth link between a host and a digital video camera.

2. Description of Related Art

A digital image represents a two-dimensional array of samples, where each sample is called a pixel. Precision determines how many levels of intensity can be represented and is expressed as the number of bits/sample. Resolution of an image refers to its capability to reproduce fine details. Higher resolution requires more complex imaging systems to represent these images in real-time. In video systems, resolution refers to the number of line pairs resolved on the face of the display screen, expressed in cycles per picture height, or cycles per picture width. Full motion video is characterized with at least 24-Hz frames/sec, and 30 or even 60 frames/sec for high definition TV. For animation, acceptable frame rate is in the range of 15-19 frames/sec while for video telephony it is 5-10 frames/sec. Videoconferencing and interactive multimedia applications require the rate of 15-30 frames/sec.

Commercial imaging applications are surfacing in digital broadcast television, compact disk video, multimedia, video teleconferencing systems, dynamic medical imaging devices, and high definition TV. Imaging applications are time critical and computationally and data intensive, and require both the storage

and transmission of enormous data sets which can be accomplished with image compression. Achieving the compression ratios necessary for digital video involves the processing of individual images to remove spatial redundancies and a motion analysis of the sequence to remove temporal redundancies.

The latest models of still and video cameras are solid-state cameras which use silicon chips for image data arrays. Since the size of the camera and the chip should be kept small, these cameras have to keep low the number of sampled image data transferred from the camera to an accompanying host image processing device. Furthermore, the mass consumers of the digital video cameras are used to viewing video images on TV at the frame rate of 30 frames per second. The currently available buses between digital video cameras and the host system have a limited bandwidth of less than 8 frames per second, which limits the number of video frames that can be transferred from the camera to the host and provides fuzzy pictures. These buses do not allow real-time video data transmission.

In order to attract the average user to purchase a digital camera, the throughput of data through a low bandwidth transmission channel between the camera and the host has to be improved by compression. The real time image processing presently involves at least three types of tradeoffs: performance versus image resolution, performance versus storage size, and performance versus input and output bandwidth. The quality of performance is influenced by the cost. Expensive compression schemes, such as MPEG, are not cost effective for low cost single chip cameras. The basic measure for the performance of a compression algorithm is compression ratio, defined as a ratio of original data size and compressed data size. There is a trade-off between the compression ratio and the picture quality. Higher compression ratios may produce lower picture quality. Quality of compression can also vary according to source image characteristics and scene content.

Therefore, there is a need for a low cost method which can improve the data bandwidth between the digital video camera and the host by applying video compression to the digital video stream before the video frame is transmitted to the host computer, which is capable of generating sharp, high quality color images in real time. Furthermore, there is a need for small and inexpensive digital solid-state video cameras capable of transferring 30 video frames per second. These cameras have to have a low gate count and low power requirements so that the size and cost of the camera is minimal.

OBJECTS AND SUMMARY OF THE INVENTION

It is a primary object of the present invention to overcome the aforementioned shortcomings associated with the prior art and to provide an image processing device which uses a low cost video compression method which is capable of generating sharp, high quality color images in real time.

Another object of the present invention is to provide a compression method which performs separate compression in the Y domain and the Cr/Cb domain.

Yet another object of the present invention is to provide a compression method with minimum computational complexity which can be implemented in hardware.

Still another object of the present invention is to provide small and inexpensive digital solid-state video cameras capable of transferring more than 20 video frames per second, which have a low gate count and low power requirements.

These as well as additional objects and advantages of the present invention are achieved by a video compression method that performs separate luminance (Y) domain compression of the video data on a line-by-line basis, without storing video data lines or video data frames, and separate chrominance

(Cr/Cb) domain averaging of the video data on a region-by-region basis without storing video data in video frames. The Y and Cr/Cb domain compression steps are implemented in the digital solid-state imaging device hardware for real time link transmission of the compressed video data to the host computer.

The method of the present invention is implemented in a pixel processing controller of the digital imaging device, such as a solid-state camera, working in isochronous traffic mode in the YCbCr 4:2:0 or 4:2:2 format, and adapted for a bandwidth-limited bus with isochronous pipes, one transmitting the Y domain values and another transmitting the Cr/Cb domain values. The Y domain compression module is adapted to determine pixels in the video line which are tagged on a pixel-by-pixel basis, according to differences in the pixel luminance values, and lengths between the tagged pixels. The Cr/Cb domain compression module is adapted to calculate a single average value for a plurality of Cr locations, and a single average value for a plurality of Cb locations.

In one embodiment of the present invention the Cr/Cb domain compression module obtains a single Cr value for each four Cr values, and a single Cb value for each sixteen Cb values in the 4:2:0 format, or a single Cr value for each eight Cr values, and a single Cb value for each thirty-two Cb values in the 4:2:2 format. In another embodiment of the present invention the compressed data is encoded and codes concatenated separately in the Y domain and in the Cr/Cb domain, before the transmission to the host computer. The concatenation in the Cr/Cb domain produces alternative Cr-only lines and Cr/Cb lines, where each Cr-only line has only Cr values, and each Cr/Cb line has alternating Cr and Cb values.

DO YOU WANT TO ADD THESE DRAWINGS?

BRIEF DESCRIPTION OF THE DRAWINGS

The objects and features of the present invention, which are believed to be novel, are set forth with particularity in the appended claims. The present

WE MAY HAVE TO

THIS CAN BE DONE AT EXAMINERS REQUEST.

SINCE ~~IF~~ WE CLAIM CONCATENATION

invention, both as to its organization and manner of operation, together with further objects and advantages, may best be understood by reference to the following description, taken in connection with the accompanying drawings.

Figure 1 is a schematic illustration of the positions of the Y,Cb,Cr sample sites on the scan lines of an interlaced picture, as used in the conventional 4:2:2 YCbCr format of the prior art.

Figure 2 is a schematic illustration of the sample site positions in a frame buffer, as used in the 4:2:2 YCbCr format of Figure 1.

Figure 3 is a schematic illustration of the positions of the Y,Cb,Cr sample sites on the scan lines of a non-interlaced picture, as used in the conventional 4:2:0 YCbCr format of the prior art.

Figures 4A and 4B are schematic illustrations of the flow chart of a method embodiment of the present invention.

Figure 5 is a schematic illustration of a digital video camera, a host, and a link between them, according to a preferred embodiment of the present invention.

Figure 6 is a schematic illustration of the tagging scheme performed in the Y domain on a single active video line of a CIF size video frame, according to a preferred embodiment of the present invention.

Figure 7 is a schematic illustration showing the Cr averaging scheme performed in the Cr/Cb domain, according to a preferred embodiment of the present invention.

Figure 8 is a schematic illustration showing the Cb averaging scheme performed in the Cr/Cb domain, according to a preferred embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The following description is provided to enable any person skilled in the art to make and use the invention and sets forth the best modes contemplated by the inventors of carrying out their invention. Various modifications, however, will remain readily apparent to those skilled in the art, since the general principles of the present invention have been defined herein specifically to provide a device and a method for maximizing the throughput of digitized video data on the bandwidth-limited link between a host and a digital video camera, which preferably use the YCbCr color system.

The YCbCr color system was developed as part of Recommendation ITU-R BT.601 during the development of a worldwide digital component video standard. Y values are defined to have a nominal range of 16 to 235, and Cb and Cr values are defined to have a range of 16 to 240, with the 128 level corresponding to zero. There are several YCbCr sampling formats, such as 4:4:4, 4:2:2, 4:1:1, and 4:2:0.

Figure 1 illustrates the positions of the Y,Cb,Cr sample sites on the scan lines of an interlaced picture, as utilized in the 4:2:2 YCbCr format, often used in consumer video applications. In this system each sample has a Y, a Cb, and a Cr value. For every two horizontal Y samples, there is one Cb and one Cr sample. Each sample typically has 8 bits per component in consumer applications or 10 bits per component in editing applications. If a frame buffer, which has all three color components for each pixel, is used, each sample in consumer applications therefore requires 16 bits per pixel or 20 bits for editing applications, usually formatted as shown in Figure 2, where the pixel numbers are given after the dash line. For display, the Y samples for which no Cb and Cr data have been saved typically have to use interpolated Cb and Cr data from the previous and next samples that have the Cb and Cr data.

Figure 3 represents 4:2:0 coded picture sampling with the positions of the Y,Cb,Cr sample sites on the scan lines of a non-interlaced picture, as used in the 4:2:0 YCbCr format, utilized by the H.261 and H.263 video teleconferencing standards and the MPEG video compression standard. The 4:2:0 YCbCr format implements a 2:1 reduction of Cb and Cr in both the vertical and horizontal directions.

The video compression method implemented in the preferred embodiment of the present invention operates in the YCbCr 4:2:0 or 4:2:2 format mode and is applied to the 4:2:0 or 4:2:2 data stream, although it may operate in other color systems and format modes, as well. Because much better fidelity in the image can be preserved by not mixing together the color and brightness information, the method preferably operates on digital video cameras which have separate chrominance and luminance signals. Therefore the preferred method of the present invention operates in two separate domains, the Y (luminance) domain and the Cr/Cb (chrominance) domain.

A flow chart of the preferred method of the present invention is shown in Figures 4A and 4B. The method operates on one video line at the time, and thus does not require lengthy frame buffers for its implementation. When applied in the Y domain the method operates in real-time and treats each horizontal video line as a separate entity, on a pixel-by-pixel basis. Therefore, in the Y domain there is no inter-frame or interline data correlation, because there is no need to save data before the transfer on a bus, and no line buffer is needed, thus saving space, cost and transfer time. The bus may be the Universal Serial Bus (USB) or another serial or parallel bus. The method is based on tagging pixels in a video line according to the differences in their luminance (Y) values. The value of a threshold for detecting a change in the luminance value between pixels can be predetermined and is programmable, as shown in step 13. The threshold value controls the image quality; the lower the threshold, the higher the image quality. In step 15 pixels' Y

values are received one by one and pixels to be tagged are determined in step 17. The Y domain compression is performed in step 19.

In the Cr/Cb domain an averaging step 21 is used to obtain the averaged Cr and Cb values for a transfer video block. Thus, in the Cr/Cb domain, a line buffer 24, shown in Figure 5, is needed by the averaging step 21 and is used to hold one or, at most, two lines of digitized pixel data. In addition, to avoid streaking in the displayed image, the maximum size of a transfer field, containing pixel information, is limited in the step 13 to a finite and programmable value.

The preferred method of the present invention is implemented within a digital video camera 10, attached to a host computer 28 via a bus 30, as shown in Figure 5. The host computer 28 is preferably a personal computer, capable of handling fast calculations and storing large amounts of data. The digital electronic camera 10 has an image sensor array 12, which may be covered with a color filter mosaic called a color filter array (CFA) 14. The method of the present invention may also be applied to monochrome cameras, in which case there is no Cr and Cb data.

In the digital video camera 10 the analog signal coming from the image sensor array 12 is digitized using an analog-to-digital converter 16. The digital video camera 10 of the invention contains its own Pixel Processing Controller (PPC) 26, which is preferably an Application Specific Integrated Circuit (ASIC) chip, which has a Y domain compression module 20 for tagging the pixel locations, and a Cr/Cb domain compression module 22 for averaging the Cr and Cb values. The PPC 26 may also be used, if needed, to transform the image data from the camera's color system (such as RGB) to another color system, such as YCbCr, in which the luminance and the chrominance values are separated, and to perform compression in the 4:2:2 or 4:2:0 format.

The PPC chip 26 has a limited-size on-board data storage area 29 to store a limited number of data values and parameters needed for the video

compression. The size of the on-board data storage area 29 is directly related to a predetermined value chosen in the step 13 for the maximum number of pixels allowed between the tagged pixels, which has to be kept small to obtain good resolution, and is preferably only 8 to 16 pixels. After the compression, the data is transferred to the host computer 28 which has a bus controller 34, a microprocessor 38, and a data storage area 36. The host computer 28 has to perform data decompression and data transformation from the YCbCr domain into the RGB domain before displaying the video frames on a display 40.

The preferred method of the present invention uses a Y domain compression algorithm and a Cr/Cb domain compression algorithm. Figure 6 illustrates how the Y domain tagging is performed on a single active video line of a CIF-size video frame, according to the preferred method of the present invention. The active pixels on the line are indicated as incoming pixels 1 through 352, represented with the symbol Y_i. Y_t represents the Y value for the previously tagged pixel. L_t represents the length associated with the tagged pixel Y_t. The variable L_t has the value obtained with a counter of the step 15 and represents the number of pixels since the last tagged pixel. Y_{th} represents the threshold value used for tagging, preferably saved with the Y_t, and L_t values in the camera data storage area 29.

The Y compression algorithm calculates the absolute value of the difference between an incoming pixel's Y_i value and the Y_t value of the previously tagged pixel in step 17. If the absolute value of the difference exceeds the threshold Y_{th}, preferably set by the host microprocessor 38, the Y_i value for this incoming pixel and the number of pixels since the last tagged pixel (length L_t) are saved in the data storage area 29 of the camera PPC chip 26. This pixel becomes the new tagged pixel and the process is repeated for new pixels until the end of the current video line is reached. The tagged pixel luminance and length values are transmitted to the host computer 28 in step 50 where they are

used in a decompression and interpolation software program 60 stored in the host data storage area 36, to reconstruct the video, through replication and/or interpolation of the values between the tagged pixels on the video line. The process is repeated for the next video line.

The host computer 28 receives the compressed video stream from the camera 10 and uses two algorithms in the interpolation software program 60 for decompressing and regenerating the original 4:2:0 or 4:2:2 image. These algorithms are applied to the Y domain and the Cr/Cb domain separately. Decompression in the Cr/Cb domain is a method opposite of the averaging method described below. In the Y domain, the decompression includes interpolation between the tagged pixels, which may be accomplished by copying a single pixel a number of times, based on the length value in the Y domain.

Figure 6 illustrates a single active video line where blank circles represent incoming pixels Y_i 63, chosen from a group of pixels $Y_1 - Y_{352}$, and shaded circles represent tagged pixels Y_{t1}, Y_{t2}, 65. L_{t1} and L_{t2} represent values of the length 67 associated with each tagged pixel 65. For example, the tagged pixel Y_{t1} has the length L_{t1} of four because it has four pixels associated with it, while Y_{t2} has the length L_{t2} of three.

The goal of the video compression method of the present invention is to minimize the number of tagged pixels transmitted to the host as well as to shorten the transfer field size. Therefore, if the length for each tagged pixel is kept beyond 16 pixels it can be represented with a field of 4 bits. In order to further increase the maximum length size, the length representing the number of pixels in a run associated with a tagged pixel may be encoded in the camera 10, after the step 19, and decoded in the host computer 28. In addition, the actual implementation of the Y domain compression method of the present invention may require use of special limitations, such as regarding the beginning and end of the video line.

Figures 7 and 8 show the averaging scheme for the Cr/Cb domain, used in an averaging step 21, and performed in the Cr/Cb compression module 22 of the digital camera PPC 26. In the Cr/Cb domain a single Cr value is calculated as the average value for preferably four Cr values in the 4:2:0 format, and for eight Cr values in the 4:2:2 format. A single Cb value is calculated to represent all Cb values in a group of pixels. In a block of 8x8 pixels there are preferably sixteen Cb values in the 4:2:0 format, and thirty-two Cb values in the 4:2:2 format. Although the averaging reduces the precision of the color information, it is permissible in many types of video applications, as in video conferencing. If the data is in the 4:2:2 format, the 4:2:2 to 4:2:0 format compression has to be performed in a method step 11 of Figure 4A on the Cr and Cb data. Y values do not change between the 4:2:2 and 4:2:0 formats.

The algorithm of the step 21 performs averaging within each region of the Cr/Cb domain, and obtains a single Cr and a single Cb value for each region. In the 4:2:0 format, in the Cr domain this ratio is preferably 4:1, because four Cr values are averaged into a single Cr value, and in the Cb domain the ratio is preferably 16:1, because sixteen Cb values are averaged into a single Cb value. In the 4:2:2 format, in the Cr domain this ratio is preferably 8:1, because eight Cr values are averaged into a single Cr value, and in the Cb domain the ratio is preferably 32:1, because thirty-two Cb values are averaged into a single Cb value. Therefore, the Cr/Cb domain averaging algorithm of step 21 needs the short line buffer 24 to save data for this compression scheme.

Figure 7 illustrates the Cr domain, 4:2:0 format, 4:1 averaging of the present invention, wherein each blank circle represents a Y value 81, a circle with an "x" symbol represents a Cr value 83, each dark circle represents a Cb value 85, and each circle with a symbol "-" represents an average Cr value 87. In this method, four adjacent Cr values are used to generated a single averaged Cr value 87, as shown in Figure 7. This calculated average Cr value 87 is sent to

the host computer 28 in the step 50 and is used to reconstruct the Cr values for this region of the video line. The rest of the Cr values for the video frame is calculated in the same manner.

Figure 8 illustrates the Cb domain, 4:2:0 format, 16:1 averaging of the present invention wherein each blank circle represents a Y value 91, each dark circle represents a Cr value 93, a circle with a symbol "=" represents a Cb value 95, each circle with a symbol "+" represents a partial average Cb value 97, and each light-shaded circle represents an average Cb value 99. Four adjacent Cb values are used to generated a single intermediate averaged Cb value 97, as shown in Figure 8. This intermediate value 97 is averaged with three other values calculated similarly and the result is sent to the host computer 28 and used to reconstruct the Cb values for this region of the video line. The rest of the Cb values for the video frame are calculated in the same manner.

The data obtained with the preferred method of the present invention may be further compressed by concatenating and/or encoding the information. For example, in the Y domain, because every tagged pixel in the image is preferably represented with an 8-bit Y value and the length with a 4-bit length value, the two 4-bit length codes for two pixels may be concatenated into a single byte. A similar method may be used in the Cr/Cb domain, because the number of Cr and Cb values for every frame is constant and known, and there are 88 Cr values in each of 72 Cr lines per frame, and there are 44 Cb values in each of 36 Cb lines per frame. The compressed Cr/Cb format for a full video frame, according to the Cr/Cb compression algorithm of the present invention, may have the alternative Cr-only and Cr/Cb lines, where each Cr-only line has only Cr values, and is followed by the Cr/Cb line of alternating Cr and Cb values.

The principles of the present invention have been proven by experimentation, using the preferred embodiments of the present invention and compared with the conventional video compression methods. The obtained

results have proven the feasibility and superiority of the present invention. The method of the invention was applied to a digital video camera with the USB bus working in an isochronous traffic mode. The USB bus is an isochronous bus which has two isochronous pipes with guaranteed, regularly scheduled, transfer of digital data. The bus pipes may be used to separately transmit compressed or uncompressed Y and Cr/Cb data, one domain per each pipe.

The preferred method of the present invention has been applied to the USB-based digital video camera. The USB-based digital video camera typically contains an external buffer memory and may support three different modes: with no external buffer memory, with an external buffer memory of 32 Kbytes, and with an external buffer memory of 128 Kbytes. It has been confirmed that the video compression algorithm of the present invention allows the camera to transfer a higher number of frames to the host than do conventional methods, depending on the compression ratio and the USB bandwidth available. Furthermore, the data transfer of CIF-size frames between the camera and the host has been performed with the higher rate even without using an external frame buffer, or when only a smaller, 32K byte frame buffer is used.

The preferred method of the present invention is able to perform fast compression and decompression and enable real time transmission with a low average compression ratio of about 3:1 for moderately complex color images, as required for the USB bus, while preserving a high degree of image sharpness. With this method CIF-size video frames, having 352 pixels per line and 288 lines per frame, can be transmitted to the host at the average rate of between 20 and 30 frames per second, with good resolution. It should be noted however that, as with the other video compression algorithms, the actual achieved compression ratio depends on the amount of detail and motion in the particular video frame sequence. An additional benefit of the present invention includes the feature that allows the change of the compression ratio with the threshold value Y_{th}.

Moreover, much higher compression ratios, such as 10:1, may be obtained when needed to squeeze image sequences through relatively low bandwidth transmission channels, such as for consumer delivery of moving images or when applied to applications that do not require very high quality, such as in video conferencing.

In another aspect of the present invention a frame rate control algorithm is implemented, which works in conjunction with the compression algorithm and allows the user to request a specific frame rate. The host computer 28, with the knowledge of the available bus bandwidth and the size of the host data storage area 36, calculates the required number of bytes per frame to achieve the selected frame rate. The host computer 28 then calculates and sets the value of the maximum length size, as well as the Y_{th} value, and sends these parameters to the camera 10.

The preferred embodiments of the present invention are capable of producing digital imaging devices with a low gate count and power requirements, thus small, inexpensive, and yet capable of transferring 30 video frames per second.

Although illustrated on a USB-based digital video camera, are believed to be applicable to other types of still and video cameras which use silicone chips, such as CIF cameras using a CCD detector. It is understood that the principles of this invention are particularly applicable to low cost digital imaging devices which have to perform on-the-fly video compression and transmit samples on a bus with the limited data bandwidth, which must perform data interpolation before the image is further processed and displayed. Such devices may be office automation digital linear sensors, digital fingerprint detectors, digital scanners, digital broadcast television, compact disk video, multimedia, video conferencing systems, desktop face-to-face visual communications (videophone), dynamic medical imaging

devices, high definition TV, video cassette recorders, copy machines, and fax machines.

Those skilled in the art will appreciate that various adaptations and modifications of the just-described preferred embodiment can be configured without departing from the scope and spirit of the invention. For instance, while the present invention has been described for the equipment using the USB bus, it is understood that the appropriately modified features of the present invention may be used to handle different buses and network channels, even wire optical fibers and broadcast channels. Furthermore, although shown on digital video cameras using the YCbCr system and CIF-size format, the present invention is equally applicable in the systems with other formats and color methods, for interlaced or non-interlaced picture. Therefore, it is to be understood that, within the scope of the appended claims, the invention may be practiced other than as specifically described herein.

CLAIMS

What Is Claimed Is:

1. A video compression method for maximizing a throughput of digitized video data on a link between a digital solid-state imaging device and a host computer, comprising the steps of:

performing the luminance (Y) domain compression of the video data on a line-by-line basis without storing video data lines or video data frames; and

performing the chrominance (Cr/Cb) domain averaging of the video data on a region-by-region basis without storing video data frames,

wherein said Y and Cr/Cb domain compression steps are implemented in the digital solid-state imaging device hardware for real time link transmission of the compressed video data to the host computer.

2. The video compression method of claim 1 wherein the link is a bandwidth-limited USB bus, and the digital solid-state imaging device is an USB-based camera which comprises a pixel processing controller with a low gate count, and is adapted to be small, inexpensive, and capable of transferring 30 video frames per second.

3. The video compression method of claim 1 wherein the step of the Y domain compression comprises the following steps:

determining a value of a threshold for detecting a change in the luminance value between pixels in a video line;

tagging pixels in the video line on a pixel-by-pixel basis, according to differences in their luminance values, said tagging step comprising the following steps:

calculating the absolute value of a difference between an incoming pixel luminance value and a previously tagged pixel luminance value, and

if the absolute value of the difference exceeds the threshold value, saving the incoming pixel luminance value as a new tagged pixel luminance value and the number of pixels since the previously tagged pixel as a length; and

transmitting the new tagged pixel luminance value and length to the host computer.

4. The video compression method of claim 1 further comprising a step of transforming the Cr/Cb data to YCbCr 4:2:0 or 4:2:2 format, said step adapted to be performed before the Cr/Cb domain compression step.

5. The video compression method of claim 1 wherein the step of the Cr/Cb domain compression comprises the following steps:

calculating a single average value for a plurality of Cr locations;

calculating a single average value for a plurality of Cb locations; and

transmitting the average Cr and Cb values to the host computer.

6. The video compression method of claim 5 wherein the step of calculating the single average value for the plurality of Cr locations comprises the step of obtaining a single Cr value for each four Cr values in the 4:2:0 format, and obtaining a single Cr value for each eight Cr values in the 4:2:2 format.

7. The video compression method of claim 5 wherein the step of calculating the single average value for the plurality of Cb locations comprises the step of obtaining a single Cb value for each sixteen Cb values in the 4:2:0 format, and obtaining a single Cb value for each thirty-two Cb values in the 4:2:2 format.

8. The video compression method of claim 7 wherein the step of calculating the single average value for the plurality of Cb locations comprises the following steps:

averaging four-by-four adjacent Cb values from a region to generate a single intermediate average Cb value for each said four Cb values; and

averaging the intermediate average Cb values to obtain a single average Cb value.

9. The video compression method of claim 1 wherein the digital solid-state imaging device is chosen from a group which consists of office automation digital linear sensors, digital fingerprint detectors, digital scanners, digital broadcast television, compact disk video, multimedia, video teleconferencing systems, dynamic medical imaging devices, high definition TV, video cassette recorders, copy machines, and fax machines, and said bus is chosen from a group which consists of computer buses, network channels, wire optical fibers, and broadcast channels.

10. The video compression method of claim 1 further comprising the steps of:

encoding the compressed data with a minimum number of bits; and

concatenating the bits of the codes representing the compressed data, wherein said concatenation is performed separately in the Y domain and in the Cr/Cb domain, and the encoding and concatenating steps are performed before the transmission to the host computer.

11. The video compression method of claim 1 wherein said step of concatenation in the Cr/Cb domain produces alternative Cr-only lines and Cr/Cb lines, where each Cr-only line has only Cr values, and each Cr/Cb line has alternating Cr and Cb values.

12. In a digital video imaging device which works in the YCbCr 4:2:0 or 4:2:2 format and is attached to a host computer via a link, a pixel processing controller comprising:

a Y domain compression module for tagging pixel locations in the Y domain according to a predetermined criteria;

a Cr/Cb domain compression module for averaging the Cr and the Cb values in the Cr/Cb domain;

in the Y domain a predetermined threshold value for detecting a change in the luminance value between pixels in a video line; and

in the Y domain a predetermined value for maximum number of pixels allowed between the tagged pixels.

13. The controller of claim 12 wherein the link is a bandwidth-limited USB bus, the digital video imaging device is a solid-state USB-based camera, and the pixel processing controller has a low gate count, and is adapted to be small, inexpensive and capable of transferring 30 video frames per second.

14. The controller of claim 12 wherein the link is a bandwidth-limited bus with isochronous pipes, the digital video imaging device is a solid-state camera working in isochronous traffic mode, and each bus pipe transmits one domain per pipe.

15. The controller of claim 12 wherein the predetermined threshold value and the predetermined value for maximum number of pixels allowed between the tagged pixels are supplied by the host computer.

16. The controller of claim 12 wherein:

the Y domain compression module is adapted to determine pixels in a video line which should be tagged on a pixel-by-pixel basis, according to the predetermined criteria based on the differences in pixel luminance values; and

the imaging device transmits the tagged pixel luminance values and lengths in the video line between the tagged pixels to the host computer.

17. The controller of claim 12 wherein the Cr/Cb domain compression module is adapted to calculate a single average value for a plurality of Cr locations and a single average value for a plurality of Cb locations, the compressed data are encoded with a minimum number of bits, and the bits of the codes representing the compressed data are concatenated separately in the Y domain and in the Cr/Cb domain, before the transmission to the host computer.

18. The controller of claim 12 wherein the Cr/Cb domain compression module is adapted to obtain a single Cr value for each four Cr values, and a single Cb value for each sixteen Cb values in the 4:2:0 format, and a single Cr value for each eight Cr values, and a single Cb value for each thirty-two Cb values in the 4:2:2 format.

19. A digital imaging device attached to a host computer via a link, comprising:

an image sensor array for obtaining luminance (Y) and chrominance (Cr, Cb) values of pixels in a video line; and

a pixel processing controller having:

a Y domain compression module for tagging pixel locations in the Y domain, and

a Cr/Cb domain compression module for averaging the Cr and the Cb values in the Cr/Cb domain.

20. The digital imaging device of claim 19 wherein said link is a bandwidth-limited bus with isochronous pipes, wherein a first bus pipe transmits the Y domain values and a second bus pipe transmits the Cr/Cb domain values, and the digital imaging device is a solid-state camera working in isochronous traffic mode in the YCbCr 4:2:0 or 4:2:2 format.

21. The digital imaging device of claim 20 wherein:

the Y domain compression module is adapted to determine pixels in the video line which are tagged on a pixel-by-pixel basis, according to differences in the pixel luminance values;

the camera transmits to the host computer the tagged pixel luminance values and lengths between the tagged pixels; and

the Cr/Cb domain compression module is adapted to calculate a single average value for a plurality of Cr locations, and a single average value for a plurality of Cb locations.

22. The digital imaging device of claim 21 wherein:

the Cr/Cb domain compression module is adapted to obtain a single Cr value for each four Cr values, and a single Cb value for each sixteen Cb values in the 4:2:0 format, and a single Cr value for each eight Cr values, and a single Cb value for each thirty-two Cb values in the 4:2:2 format;

said compressed data are encoded and codes are concatenated separately in the Y domain and in the Cr/Cb domain, before the transmission to the host computer; and

said concatenation in the Cr/Cb domain produces alternative Cr-only lines and Cr/Cb lines, where each Cr-only line has only Cr values, and each Cr/Cb line has alternating Cr and Cb values.

ABSTRACT OF THE DISCLOSURE

A video compression method is provided and implemented in a pixel processing controller of a digital solid-state imaging device for maximizing throughput of digitized video data on a link between the digital solid-state imaging device and a host computer. The method performs separate luminance (Y) domain compression of the video data on a line-by-line basis, without storing video data lines or video data frames, and separate chrominance (Cr/Cb) domain averaging of the video data on a region-by-region basis without storing video data in video frames. The Y and Cr/Cb domain compression steps are implemented in the digital solid-state imaging device hardware for real time link transmission of the compressed video data to the host computer.

JOSEPH W. PRICE
ALBIN H. GESS
FRANKLIN D. UBELL
DOYLE B. JOHNSON
MICHAEL J. MOFFATT
GORDON E. GRAY III
BRADLEY D BLANCHE*
SANDRA M. PARKER

*ADM. VA ONLY

PRICE, GESS & UBELL
ATTORNEYS AT LAW

2100 S.E. MAIN STREET, SUITE 250

IRVINE, CALIFORNIA 92614-6238

A PROFESSIONAL CORPORATION
TELEPHONE (714) 261-8433
FACSIMILE: (714) 261-9072
FACSIMILE (714) 261-1726

e-mail: pgu@ix.netcom.com

COMBINED DECLARATION AND POWER OF ATTORNEY

Applicant: BEHNAM S. KATIBIAN, et al.

For: METHOD AND APPARATUS FOR LOW-COST LINE-BASED VIDEO COMPRESSION OF DIGITAL VIDEO STREAM DATA

Attorneys' Docket: ROC1-BC20/97RSS423

EXPRESS MAIL LABEL NO. EM322760409US

DATE OF DEPOSIT: March 13, 1998

Docket No. ROC1-BC20/97RSS423

DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first, and sole inventor (if only one name is listed below) or an original, first, and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled **Method And Apparatus For Low Cost Line-Based Video Compression Of Digital Video Stream Data**, the specification of which

(check one) ☒ is attached hereto ☐ was filed on
as Application Serial No.
and was amended on (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, § 1.56(a).

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)	(Filing Date)	(Status patented, pending, abandoned)
(Application Serial No.)	(Filing Date)	(Status patented, pending, abandoned)

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

William C. Cray, Reg. No. 27,627; Phillip K. Yu, Reg. No. 35,742; Susie H. Oh, Reg. No. 36,391; Joseph W. Price, Reg. No. 25,124; Albin H. Gess, Reg. No. 25,726; Franklin D. Ubell, Reg. No. 27,009; Michael J. Moffatt, Reg. No. 39,304; Doyle B. Johnson, Reg. No. 39,240, Bradley D. Blanche, Reg. No. 38,387, and Sandra M. Parker, Reg. No. 36,233, with full power of substitution and revocation hereby given to William C. Cray.

Address all telephone calls to Albin H. Gess at telephone no. (714) 261-8433

Address all correspondence to Albin H. Gess
Price, Gess & Ubell
2100 S.E. Main Street, Suite 250
Irvine, California 92614-6238

DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of first joint inventor: Magued M. Bishay

Inventor's Signature:  Date: March 12, 1998

Residence: 1411-1/2 Cliff Drive, Newport Beach, California 92663 Citizenship: Egypt

Post Office Address: 1411-1/2 Cliff Drive, Newport Beach, California 92663

Full name of second joint inventor: Behnam S. Katibian

Inventor's Signature: Date: March 12, 1998

Residence: 1375 Kelton Avenue, No. 207, Los Angeles, California 90024 Citizenship: U.S.A.

Post Office Address: 1375 Kelton Avenue, No. 207, Los Angeles, California 90024

Full name of third joint inventor: _____

Inventor's Signature: _____ Date: _____

Residence: _____ Citizenship: _____

Post Office Address: _____

JOSEPH W PRICE
ALBIN H. GESS
FRANKLIN D. UBELL
DOYLE B. JOHNSON
MICHAEL J. MOFFATT
GORDON E. GRAY III
BRADLEY D. BLANCHE*
SANDRA M. PARKER

*ADM. VA ONLY

PRICE, GESS & UBELL
ATTORNEYS AT LAW

2100 S.E. MAIN STREET, SUITE 250

IRVINE, CALIFORNIA 92614-6238

A PROFESSIONAL CORPORATION
TELEPHONE: (714) 261-8433
FACSIMILE: (714) 261-9072
FACSIMILE (714) 261-1726

e-mail: pgu@ix.netcom.com

DRAWING COVER SHEET

Applicant: BEHNAM S. KATIBIAN, et al.

For: METHOD AND APPARATUS FOR LOW-COST LINE-BASED VIDEO COMPRESSION OF DIGITAL VIDEO STREAM DATA

Attorneys' Docket: ROC1-BC20/97RSS423

EXPRESS MAIL LABEL NO. EM322760409US

DATE OF DEPOSIT: March 13, 1998



Figure 1
(PRIOR ART)

PIXEL 0	PIXEL 1	PIXEL 2	PIXEL 3	PIXEL 4	PIXEL 5
Y7-0	Y7-1	Y7-2	Y7-3	Y7-4	Y7-5
Y6-0	Y6-1	Y6-2	Y6-3	Y6-4	Y6-5
Y5-0	Y5-1	Y5-2	Y5-3	Y5-4	Y5-5
Y4-0	Y4-1	Y4-2	Y4-3	Y4-4	Y4-5
Y3-0	Y3-1	Y3-2	Y3-3	Y3-4	Y3-5
Y2-0	Y2-1	Y2-2	Y2-3	Y2-4	Y2-5
Y1-0	Y1-1	Y1-2	Y1-3	Y1-4	Y1-5
Y0-0	Y0-1	Y0-2	Y0-3	Y0-4	Y0-5
CB7-0	CR7-0	CB7-2	CR7-2	CB7-4	CR7-4
CB6-0	CR6-0	CB6-2	CR6-2	CB6-4	CR6-4
CB5-0	CR5-0	CB5-2	CR5-2	CB5-4	CR5-4
CB4-0	CR4-0	CB4-2	CR4-2	CB4-4	CR4-4
CB3-0	CR3-0	CB3-2	CR3-2	CB3-4	CR3-4
CB2-0	CR2-0	CB2-2	CR2-2	CB2-4	CR2-4
CB1-0	CR1-0	CB1-2	CR1-2	CB1-4	CR1-4
CB0-0	CR0-0	CB0-2	CR0-2	CB0-4	CR0-4

Figure 2
(PRIOR ART)



Figure 3
(PRIOR ART)


START
PERFORM FORMAT CONVERSION FROM 4:2:2 TO 4:2:0 MODE, IF NEEDED
11
DETERMINE PARAMETER VALUES, SUCH AS Y_{tL}, MAXIMUM LENGTH, TRANSFER FIELD SIZE
13
ENTER NEXT PIXEL VALUE & INCREMENT A LENGTH COUNTER
15
CALCULATE $|Y_i - Y_t|$
17
$|Y_i - Y_t| > Y_{tL}$
YES
PERFORM Y DOMAIN COMPRESSION
19
NO
21
PERFORM IN C_r/C_b DOMAIN
A

FIGURE 4A



Figure 4B



Figure 6



Figure 5

09042124.031398



Figure 7

EP 3 054 454 A1



FIGURE 8

Document - Doc ID